

INFINITY

N-type

Bifacial Module with Double Glass

DMxxxG12T-B66HSW

695~720W

23.2%
Max. Efficiency

- **Leading manufacturing**
40+ years experience in high-tech manufacturing.
- **High environmental, social and governance responsibility (ESG)**
100% green production, transparent supply chain and excellent ESG rating in the solar industry.

15
15 years
product warranty

30
30 years linear
power warranty



Top Choice For Project Applications

Improved IRR with shorter amortisation time, reduced LCOE (Levelised Cost of Energy) and lower BOS (Balance of System) costs.



Extended Stress Tests

Protection against harsh environmental conditions Certified by TÜV Rheinland.



Green Product

Focus on circular economy - low carbon footprint, PFAS-free and recyclable components.


COMPANY MANAGEMENT SYSTEM

SA 8000: ILO Standards. Social responsibility standards
ISO 9001: Quality management system
ISO 14001: Environmental management system
ISO 45001: Occupational health and safety management system
ISO 50001: Energy management system
ISO 27001: Information security management system

PRODUCT CERTIFICATION

IEC 61215, IEC 61730

POWER WARRANTY



SolarPower
Europe



Warranty partner


Munich RE

DMxxxG12T-B66HSW



Module Specification

Cell Type	N type Mono-crystalline, 132(6×22)
Dimensions (mm)	2384×1303×33
Weight (kg)	37.7
Front Cover	2mm heat strengthened glass
Rear Cover	2mm heat strengthened glass
Junction Box	3 Diodes, IP68 according to IEC 62790
Cables	4mm ² /Portrait: 350mm (+)/250mm(-) Landscape: 1300mm(+)/1300mm(-) Length can be customized
Connector Type	Sunter: PV-ZH202B; Stäubli: PV-KST4-EVO2/xy_UR, PV-KBT4-EVO2/xy_UR, PV-KST4-EVO2A/xy, PV-KBT4-EVO2A/xy



Electrical Specifications¹

Module Type	DM695G12T-B66HSW		DM700G12T-B66HSW		DM705G12T-B66HSW		DM710G12T-B66HSW		DM715G12T-B66HSW		DM720G12T-B66HSW	
Testing Condition	STC ²	BNPI ³	STC	BNPI	STC	BNPI	STC	BNPI	STC	BNPI	STC	BNPI
Maximum Power (Pmax/W)	695	768	700	774	705	779	710	785	715	790	720	796
Maximum Power Current (Imp/A)	17.30	19.09	17.35	19.15	17.40	19.20	17.45	19.26	17.50	19.31	17.54	19.36
Maximum Power Voltage (Vmp/V)	40.20	40.25	40.39	40.44	40.58	40.63	40.76	40.81	40.93	40.98	41.10	41.15
Short-circuit Current (Isc/A)	18.38	20.22	18.43	20.28	18.48	20.33	18.52	20.38	18.56	20.42	18.60	20.46
Open-circuit Voltage (Voc/V)	48.22	48.23	48.42	48.43	48.62	48.63	48.82	48.83	49.02	49.03	49.20	49.21
Module Efficiency STC (%)	22.4		22.5		22.7		22.9		23.0		23.2	

¹ Measurements according to IEC 60904-3, Measurement tolerance: Isc: ±4%, Voc: ±3%, Test uncertainty for Pmax: ±3%, Bifaciality: φPmax:80±5%; φVoc:100±3%; φIsc:80±5%

² STC (Standard Test Condition): Radiation 1000W/m², Module temperature 25°C, AM=1.5

³ BNPI: Front radiation 1000W/m², Rear radiation 135W/m², Module temperature 25°C, AM=1.5



BIFACIAL OUTPUT - REAR SIDE POWER GAIN

10 %	Pmax (STC)	765	770	776	781	787	792
20 %	Pmax (STC)	834	840	846	852	858	864
30 %	Pmax (STC)	904	910	917	923	930	936



Temperature Characteristics

Nominal Module Operating Temperature (NMOT)	42±2°C
Temperature Coefficient of Pmax (%/°C)	-0.29
Temperature Coefficient of Voc (%/°C)	-0.25
Temperature Coefficient of Isc (%/°C)	+0.048



Packaging

Container	40HQ
Pallet Dimensions (mm)	1320×1115×2502
Pieces per Pallet	33
Pieces per Container	594
Country of Manufacture	China




Hengdian Group DMEGC Magnetics Co.,Ltd.
Add: Hengdian Industrial Zone, Dongyang City Zhejiang Province, China 322118
Tel: +61 0498353593 E-mail: xin.wang@dmevc.com.cn Website: www.dmegcsolar.com



Operating Conditions

Operating Temperature (°C)	-40 to +70
Maximum System Voltage (V)	1500 DC(IEC)
Overcurrent Protection Rating (A)	35
Power Output Sorting Tolerance (%)	0~3
Protection Class	Class II
Max. Test Load, Push/Pull (Pa)	Front 5400 / Back 2400
Max. Design Load, Push/Pull (Pa)	Front 3600 / Back 1600
Fire Rating Class	IEC Class C

Current-Voltage Curve (720W)



Statement: The installation instructions and the warranty conditions must be followed. Due to technological progress, product parameters will be adjusted accordingly. When signing the contract, the latest data of the company shall prevail. All information in this data sheet corresponds to EN 50380. Changes and errors excepted. Document: EN DS-G12T-B66HSW-20241106.

©DMEGC 2024 – All Rights Reserved