

# INFINITY RT 3.0

**N-type**


Mono facial Module with Double Glass

**DMxxxG12RT-G48HSW**

**460~485W**

**24.3%**  
Max. Efficiency

- **Leading manufacturing**  
40+ years experience in high-tech manufacturing.
- **High environmental, social and governance responsibility (ESG)**  
100% green production, transparent supply chain and excellent ESG rating in the solar industry.



### Higher Module Efficiency

Increased energy yield due to optimized material use.



### Extended Stress Tests


Protection against harsh environmental conditions Certified by TÜV.



### Green Product

Focus on circular economy - low carbon footprint, PFAS-free and recyclable components.

## POWER WARRANTY



## COMPANY MANAGEMENT SYSTEM

SA 8000: ILO Standards. Social responsibility standards  
 ISO 9001: Quality management system  
 ISO 14001: Environmental management system  
 ISO 45001: Occupational health and safety management system  
 ISO 50001: Energy management system  
 ISO 27001: Information security management system

## PRODUCT CERTIFICATION

IEC 61215, IEC 61730  
 Extended-Stress (IEC TS 63209)  
 Ammonia Corrosion (IEC 62716)  
 Salt Mist Corrosion (IEC 61701)  
 LeTID (IEC TS 63342)  
 Dust & Sand (IEC 60068)



SolarPower Europe




Warranty partner

Munich RE

# DMxxxG12RT-G48HSW

## Module Specification

Cell Type	N type Mono-crystalline, 96 (6×16)
Dimensions (mm)	1762×1134×30
Weight (kg)	24.0
Front Cover	2 mm heat strengthened glass, Anti-reflective coating
Rear Cover	2 mm heat strengthened glass
Junction Box	3 Diodes, IP68 according to IEC 62790
Output Cables (Including Connector)	4 mm <sup>2</sup> /Portrait: 300 mm (+) /200 mm (-) Landscape: 1100 mm (+) /1100 mm (-) Length can be customized
Connector Type	PV-D01 or MC4-EVO 2A (1500V)



## Electrical Specifications<sup>1</sup>

Module Type	DM460G12RT-G48HSW		DM465G12RT-G48HSW		DM470G12RT-G48HSW		DM475G12RT-G48HSW		DM480G12RT-G48HSW		DM485G12RT-G48HSW	
	STC <sup>2</sup>	NMOT <sup>3</sup>	STC	NMOT	STC	NMOT	STC	NMOT	STC	NMOT	STC	NMOT
Maximum Power (Pmax/W)	460	351	465	354	470	358	475	362	480	366	485	370
Maximum Power Current (Imp/A)	15.06	12.24	15.13	12.29	15.20	12.35	15.27	12.41	15.34	12.46	15.41	12.52
Maximum Power Voltage (Vmp/V)	30.57	28.68	30.75	28.85	30.93	29.02	31.11	29.19	31.29	29.36	31.47	29.53
Short-circuit Current (Isc/A)	15.73	12.68	15.78	12.72	15.83	12.76	15.88	12.80	15.93	12.84	15.98	12.88
Open-circuit Voltage (Voc/V)	35.81	34.46	36.03	34.68	36.25	34.89	36.47	35.10	36.69	35.31	36.91	35.52
Module Efficiency STC (%)	23.0		23.3		23.5		23.8		24.0		24.3	

<sup>1</sup> Measurements according to IEC 60904-3, Measurement tolerance: Pmax:  $\pm 3\%$ , Isc:  $\pm 4\%$ , Voc:  $\pm 3\%$

<sup>2</sup> STC (Standard Test Condition): Radiation 1000 W/m<sup>2</sup>, Module temperature 25°C, AM = 1.5

<sup>3</sup> NMOT: Radiation 800 W/m<sup>2</sup>, Ambient temperature 20°C, AM = 1.5, Wind Speed 1 m/s

## Operating Conditions

Operating Temperature (°C)	-40 to +85
Maximum System Voltage (V)	1500 DC(IEC)
Overcurrent Protection Rating (A)	30
Power Sorting (%)	0~3
Protection Class	Class II
Fire Class	Class C (IEC)
Max. Test Load, Push/Pull (Pa)	Front 5400 / Back 2400
Max. Design Load, Push/Pull (Pa)	Front 3600 / Back 1600
Hail Class	HW3*


\* Reference diameter of ice balls-VKF 30mm, Ice ball storage temp -20°C.

## Packaging

Container	40HQ
Pallet Dimensions (mm)	1800x1140x1250
Pieces per Pallet	36
Pieces per Container	936

## Temperature Characteristics

Nominal Module Operating Temperature (NMOT)	42 $\pm$ 2°C
Temperature Coefficient of Pmax (%/°C)	-0.29
Temperature Coefficient of Voc (%/°C)	-0.25
Temperature Coefficient of Isc (%/°C)	+0.048



Hengdian Group DMEGC Magnetics Co.,Ltd.  
 Add: Hengdian Industrial Zone, Dongyang City Zhejiang Province, China 322118  
 Tel: 0086-579-8658-8826 E-mail: solar@dmevc.com.cn Website: www.dmevc.com

DMEGC Renewable Energy B.V.  
 Add: Industrieweg 2,2641 RM Pijnacker, The Netherlands.  
 Tel: +31 (0) 8 58200765 E-mail: contact@dmevc.eu

Statement: The installation instructions and the warranty conditions must be followed. Due to technological progress, product parameters will be adjusted accordingly. When signing the contract, the latest data of the company shall prevail. All information in this data sheet corresponds to EN 50380.Changes and errors excepted. Document: EN DS-G12RT-G48HSW -20260502.

©DMEGC – All Rights Reserved