

INFINITY RT


N-type

Bifacial Module with Double Glass

DMxxxG12RT-B54HSW

505~525W

23.4%
Max. Efficiency



Please refer to the DMEGC Standard Limited Warranty for more details about the product warranty and power warranty.



Higher Module Efficiency

Increased energy yield due to optimized material use.



Extended Stress Tests


Protection against harsh environmental conditions
Certified by T₁ V Rheinland.



Leading Manufacturing

40+ years experience in high-tech manufacturing.

POWER WARRANTY



COMPANY MANAGEMENT SYSTEM

SA 8000: ILO Standards. Social responsibility standards
ISO 9001: Quality management system
ISO 14001: Environmental management system
ISO 45001: Occupational health and safety management system
ISO 50001: Energy management system
ISO 27001: Information security management system

PRODUCT CERTIFICATION

IEC 61215, IEC 61730
Extended-Stress (IEC TS 63209)
Ammonia Corrosion (IEC 62716)
Salt Mist Corrosion (IEC 61701)
LeTID (IEC TS 63342)
Dust & Sand (IEC 60068)



Warranty partner




DMxxxG12RT-B54HSW



Module Specification

Cell Type	N type Mono-crystalline, 108(6 $\times$ 18)
Dimensions (mm)	1977 $\pm$ 1 1134 $\pm$ 30
Weight (kg)	27.1
Front Cover	2 mm heat strengthened glass, Anti-reflective coating
Rear Cover	2 mm heat strengthened glass
Junction Box	3 Diodes, IP68 according to IEC 62790
Output Cables (Including Connector)	4 mm ² /Portrait: 300 mm (+)/ 200 mm (-) Landscape: 1200 mm(+)/ 1200 mm (-) Length can be customized
Connector Type	PV-D01 or MC4-EVO 2A (1500V)



Electrical Specifications¹

Module Type	DM505G12RT-B54HSW		DM510G12RT-B54HSW		DM515G12RT-B54HSW		DM520G12RT-B54HSW		DM525G12RT-B54HSW	
Testing Condition	STC _I	NMOT _I	STC	NMOT	STC	NMOT	STC	NMOT	STC	NMOT
Maximum Power (P _{max} /W)	505	385	510	389	515	393	520	396	525	400
Maximum Power Current (I _{mp} /A)	14.80	12.03	14.84	12.06	14.88	12.09	14.92	12.12	14.96	12.16
Maximum Power Voltage (V _{mp} /V)	34.13	32.02	34.37	32.25	34.61	32.47	34.85	32.70	35.09	32.92
Short-circuit Current (I _{sc} /A)	15.73	12.68	15.78	12.72	15.83	12.76	15.88	12.80	15.93	12.84
Open-circuit Voltage (V _{oc} /V)	40.49	38.97	40.62	39.09	40.75	39.22	40.88	39.34	41.01	39.47
Module Efficiency STC (%)	22.5		22.7		23.0		23.2		23.4	

¹ Measurements according to IEC 60904-3, Measurement tolerance: P_{max}: $\pm 3\%$, I_{sc}: $\pm 4\%$, V_{oc}: $\pm 3\%$, Bifaciality: 80% $\pm 5\%$

² STC (Standard Test Condition): Radiation 1000W/m², Module temperature 25°C, AM=1.5

³ NMOT: Radiation 800W/m², Ambient temperature 20°C, AM=1.5, Wind Speed 1m/s



Electrical Specifications¹(BNPI²)

Nameplate Power (W)	505	510	515	520	525
Maximum Power (P _{max} /W)	559	564	570	575	581
Maximum Power Current (I _{mp} /A)	16.33	16.38	16.42	16.47	16.51
Maximum Power Voltage (V _{mp} /V)	34.17	34.41	34.65	34.89	35.13
Short-circuit Current (I _{sc} /A)	17.31	17.36	17.42	17.47	17.53
Open-circuit Voltage (V _{oc} /V)	40.49	40.62	40.75	40.88	41.01

¹ Measurements according to IEC 60904-3, Measurement tolerance: P_{max}: $\pm 3\%$, I_{sc}: $\pm 4\%$, V_{oc}: $\pm 3\%$

² BNPI: Front radiation 1000W/m², Rear radiation 135W/m², Module temperature 25°C, AM=1.5



Temperature Characteristics

Nominal Module Operating Temperature (NMOT)	42 $\pm$ 2 $^{\circ}$ C
Temperature Coefficient of P _{max} (%/ $^{\circ}$ C)	-0.29
Temperature Coefficient of V _{oc} (%/ $^{\circ}$ C)	-0.25
Temperature Coefficient of I _{sc} (%/ $^{\circ}$ C)	+0.048




Packaging

Container	40HQ
Pallet Dimensions (mm)	1985x1140x1250
Pieces per Pallet	36
Pieces per Container	864



Operating Conditions

Operating Temperature ($^{\circ}$ C)	-40 to +85
Maximum System Voltage (V)	1500 DC(IEC)
Overcurrent Protection Rating (A)	30
Power Sorting (%)	0~3
Protection Class	Class II
Max. Test Load, Push/Pull (Pa)	Front 5400 / Back 2400
Max. Design Load, Push/Pull (Pa)	Front 3600 / Back 1600



Hengdian Group DMEGC Magnetics Co.,Ltd.
Add: Hengdian Industrial Zone, Dongyang City Zhejiang Province, China 321118
Tel: 0086-579-8658-8826 E-mail: solar@dmegec.com.cn Website: www.dmegecsolar.com

DMEGC Renewable Energy B.V.
Add: Industrieweg 2,2641 RM Pijnacker, The Netherlands.
Tel: +31 (0) 8 58200765 E-mail: contact@dmegec.eu

Statement: The installation instructions and the warranty conditions must be followed. Due to technological progress, product parameters will be adjusted accordingly. When signing the contract, the latest data of the company shall prevail. All information in this data sheet corresponds to EN 50380. Changes and errors excepted. Document: EN DS-G12RT-B54HSW Plus-20260915.

ÉDMEGC 1 All Rights Reserved